#### **ETS EUROPE BVBA**

Herentalsebaan 406 D1. 2160 Wommelgem, Belgium Tel: +32 3 227 28 58

Fax: +32 3 475 16 66 E-Mail: info@ets-europe.be www.ets-europe.be

\_

## **EU-Declaration of Performance**

In accordance with Annex III of Regulation (EU) No.305/2011 (Construction Product Regulation)

For the product "ECO HYDRO SIL"

No: ECO HYDRO SIL

1. Unique identification code of the product-type:

EN 1504-2: ZA.1b

2. Type, batch or serial number or any other element allowing identification of the construction product

as required pursuant to Article 11(4):

Batch number: See packaging of the product

3. Intended use or uses of the construction product, in accordance with the applicable harmonized technical specification, as foreseen by the manufacturer:

#### EN 1504-9

Surface protection product – Impregnation for concrete, reinforced concrete and all cementitious substrates.

Principle 1: Protection against ingress of substances (1.2)

4. Name, registered trade name or registered trademark and contact address of the manufacturer as required pursuant to Article 11(5):

# ETS EUROPE BVBA HERENTALSEBAAN 406 D1 2160 WOMMELGEM, BELGIUM

5. Where applicable, name and contact address of the authorized representative whose mandate covers the tasks specified in Article 12(2):

## **Not Relevant**

6. System or systems of assessment and verification of constancy of performance of the construction product as set out in Annex V:

#### System 4

7. In case of the declaration of performance concerning a construction product covered by a harmonized standard:

# **Not relevant**

9. In case of the declaration of performance concerning a construction product for which a European Technical Assessment has been issued:

# Not relevant







## **ETS EUROPE BVBA**

Herentalsebaan 406 D1. 2160 Wommelgem, Belgium Tel: +32 3 227 28 58

Fax: +32 3 475 16 66 E-Mail: info@ets-europe.be www.ets-europe.be

# 9. Declared performance:

Essential Characteristic	Performance	Harmonized technical specification
Water vapour permeability:	NPD	
Water absorption und alkaline resistance:	Absorption coefficient < 7,5% compared with untreated sample < 10% in alkaline solution	
Chemical resistance:	No visible defects	EN 1504-2:2004
Loss of mass after freeze-thaw conditions:	NPD	
Pull-off test:	NPD	
Reaction to fire:	A1	
Grip:	NPD	
Penetration depth:	Class I: < 10 mm	
Dangerous substances:	None	
Impact strength:	NPD	

10. The performance of the product identified under point 1. and 2. is in conformity with the performance declared in section 9. This declaration of performance is issued under the sole responsibility of the manufacturer identified under point 4.

Signed for and on behalf of the manufacturer by:

Jean-Luc De Potter, CEO (Name and function)

[Wommelgem, 22.09.2021] (Place and date of issue)

\_\_\_\_\_ (Signature)





